

# SECURE. EFFICIENT. PROVEN.



## UBA<sup>®</sup>

UNIVERSAL BILL ACCEPTOR

The award-winning UBA is trusted and used the world over. It has the acceptance, speed and security that you and your customers demand. Keep your profits flowing with UBA's patented removable stacker mechanism and its incredible combination of powerful sensing and anti-stringing. Keep your customers happy with UBA's automatic retry feature, self-centering mechanism and faster drops with ICB<sup>®</sup> cash box.

### FEATURES

- Superior magnetic & optical sensing technology
- Accepts currencies up to 85 mm wide
- Superior anti-pullback technology
- Automatic retry feature
- Accepts currency from multiple countries simultaneously
- High-speed motors
- High impact plastic cash box
- Intelligent Cash Box capable
- Rear USB host interface
- Downloadable, flash or socketed EPROM
- Front access USB download port
- Barcode reader

### BENEFITS

- Highly secure sensing protects your profits
- Accepts most of the world's currencies
- Prevents stringing
- Increased acceptance rate
- No need to change software
- Fast processing speed
- Lightweight and damage resistant
- Better accounting
- Easy communication between game and validator
- Convenient access for software updates
- Quick and easy accessibility
- Accepts tickets for promotional flexibility



## MEMORY

- UBA-10/11 - 8 Mb
- UBA-14/24 - 16 Mb

## ESCROW

- 1 banknote

## VALIDATION SPEED

- Validation approximately 3 seconds
- Note-to-note processing speed approximately 5 seconds
- Automatic Retry if note rejected

## CASH BOX

- Compatible with WBA®-Series Cash Box
- Capacity approximately 600 notes (1000 option)
- Visual Audit Window

## INTERFACE

- UBA-10/11: Photocoupler, RS-232C
- UBA-14/24: Photocoupler, USB

## MAINTENANCE

- All major areas including the bill path are accessible without the use of tools

## CURRENCY ACCEPTED

- US & International
- Width: 60 - 85mm, length: 120 - 165mm

## CONFIGURATIONS

- Flash or socketed EPROM
- Downstack (SS) or upstack (SU)

## SOFTWARE

- Software upgrades are released for currency changes and security measures. JCM software is copyrighted to JCM American Corp.

## INSTALLATION

- Indoor use only, horizontal mounting

## POWER REQUIREMENT

- DC+12V (±5%)
- Standby: 3.6VA, Operating: 20VA (Max. 48VA)

## DIMENSIONS (HxWxD)

- 298x114x234mm (11.73x 4.49x 9.21")

## WEIGHT APPROX.

- 4kg including cash box

## APPROVALS

- CE, UL, CSA, TP

## ENVIRONMENT

- Operating: 5 to 50°C (41 to 122°F)
- Storage: -20 to 60°C (-4 to 140°F)
- Humidity: 30% to 85% RH (no condensation)

## TECHNICAL SUPPORT

- Training classes are available for all JCM products



600 Note Cash Box



Cash Box with ICB

1000 Note Cash Box



EMEA: 49.211.5306.4550 • JAPAN: 81.6.6703.8400 • US: 702.651.0000 • US: 800.683.7248

[jcmglobal.com](http://jcmglobal.com)

JCM and JCM logo are registered trademarks of Japan Cash Machine Co., Ltd. and JCM American Corporation. All other marks are registered trademarks of their respective owners. JCM reserves the right to change product specifications without notice.